


SCOREBOARD SPECIFICATIONS FOR



MODEL OSS-397



STANDARD COLORS

Optec-Sansi North America

716 S. Nogales St.
City of Industry, CA 91748
(888) 241-6603
(626) 867-7858 Fax
info@optecsansi.com

SCOREBOARD SPECIFICATIONS MODEL OSS-397

Lead your league with this Baseball/Softball scoreboard! Large 24" and 18" high super-bright 100,000-hour rated LED numerals are the largest with the widest viewing angle in the industry and are visible over 300 feet. The 22-gauge galvanized steel cabinet with powder-coat finish means your scoreboard is the most durable on the market and will look brand new for many years! Scoreboard package includes: operator's keyboard, digit protective shields, junction box cover (cable models only), mounting rails and a complete operation, installation, service manual and warranty details on the CD shipped with the scoreboard.

OVERALL DIMENSIONS

28' wide x 8' tall x 8.0" depth

WEIGHT

Hanging weight: 1070 lbs.

Shipping weight: 1500 lbs.

CONSTRUCTION

22-gauge galvanized steel cabinet with powder coat finish for strength, durability, and lasting appearance

POWER REQUIREMENTS

Scoreboard:

(1) 20-amp, 120-volt, 60-hertz, grounded AC circuit connected to an ON/OFF switch and/or circuit breaker

Controller:

Standard LCD controller powered by 12V DC Adapter or an optional internal battery.

SCORING INFORMATION DISPLAYED

AT BAT: 2-digit displays, 0-99

BALL: 1-digit display, 0-9

STRIKE: 1-digit display, 0-9

OUT: 1-digit display, 0-9

HITS / ERRORS: 2-digit displays, 0-99, H or E, and Field Position Number

INNING SCORING: 10 – 1 - digit displays, 0-9

RUNS: 2-digit displays, 0-99, Home and Guest

ERROR: 1-digit display, 0-9, Home and Guest

CAPTIONS

HOME and GUEST: 13.0" tall

AT BAT, BALL, STRIKE, OUT, and H/E: 11.0" tall

INNING SCORING, Total RUNS, Total HITS, and Total ERRORS: 10.0" tall

Polymeric Calendared Vinyl Lettering

AT BAT, BALL, STRIKE, OUT, and H/E Displays

24.0" tall, 160° visibility, red, 100,000 hour-rated, outdoor Super-Bright LED (light emitting diode) displays

Impact Resistant Acrylic Protective Digit Shields and Adjustable LED Intensity Included

INNING SCORES, RUNS, HITS, and ERROR Displays

18.0" tall, 160° visibility, red, 100,000 hour-rated, outdoor Super-Bright LED (light emitting diode) displays

Impact Resistant Acrylic Protective Digit Shields and Adjustable LED Intensity Included

APPROVALS

ETL/CSA listed

Scoreboard: Meets all FCC Class A requirements

900 MHz wireless transmitter: FCC Part 15 certified

900 MHz wireless receiver: Meets all FCC Part 15 requirements

WARRANTY

This product is warranted against defects in materials and workmanship for a period of five (5) years from the date of invoice. This includes factory repair service for parts covered under warranty. Complete warranty details are included on the CD shipped with each unit.

SERVICE

Technical Support is available 24 hours a day, 7 days a week

An access panel on the back of the scoreboard allows easy access to the electronic module, (the only working part of the scoreboard), for ease of replacement/servicing. These universal, plug-in electronic modules are used in all of the manufacturer's scoreboards using outdoor LED displays, and are 100% interchangeable between any of the manufacturer's outdoor, permanent LED scoreboards. If you have any question contact us at (888) 241-6603 x3 during business hours or 24/7 at service@optecsansi.com.

INSTALLATION

This model may be installed between (3) 14" OD steel, schedule 40 poles; or (3) 14" I-beams, minimum. Hole depth /diameter as well as pole/concrete specifications must be based on customer's local building codes, soil conditions, and wind loads. Mounting rails are supplied.

Support structure and mounting hardware supplied by installer/others

SCOREBOARD CONTROLLER

Dimensions: 2.5" height x 14.7" width x 7.0" depth.

Weight: 2.10 lbs.

The keyboard controller available with this scoreboard is microprocessor-controlled, molded of highimpact ABS plastic, has a tactile membrane keypad. Options include 900 MHz wireless control and internal battery pack with automatic battery charger.

Cable-Controlled System (standard) Includes:

- (1) Keyboard controller
- (3) BASEBALL/SOFTBALL keypad inserts
- (1) Junction box cover with receptacle (to be installed at scorekeeper's location)
- (1) 20-ft. signal cable (used to connect the keyboard to the junction box receptacle)
- (1) Project-specific length of 4 wire twisted pair, shielded control cable


900 MHz Wireless System (optional) Includes:

- (1) Universal LCD keyboard controller
- (3) BASEBALL/SOFTBALL keypad inserts
- (1) 12-volt DC wall transformer for standard model
- (1) 900 MHz transmitter (connects to keyboard controller via supplied interface cable)
- (1) 900 MHz receiver (connects to the scoreboard, eliminating control cable and junction box installation)


OPTIONS

- Wireless Remote Control System
- Wireless Remote Control Battery Option
- Solar-Charged Battery Power

Electronic Team Names
Message Center
Controller Carry Case
Sponsor Panels



Front View



Rear View