


SCOREBOARD SPECIFICATIONS FOR



MODEL OSS-772



STANDARD COLORS

Optec-Sansi North America

716 S. Nogales St.
City of Industry, CA 91748
(888) 241-6603
(626) 867-7858 Fax
info@optecsansi.com

SCOREBOARD SPECIFICATIONS MODEL OSS-772

Lead your organization with this Football scoreboard! Large 30",24" & 18" high super-bright 100,000-hour rated LED numerals are the largest with the widest viewing angle in the industry and are visible over 300 feet. The 22-gauge galvanized steel cabinet with powder-coat finish means your scoreboard is the most durable on the market and will look brand new for many years! Scoreboard package includes: operator's keyboard, digit protective shields, junction box cover (cable models only), mounting rails and a complete operation, installation and service manual. 5-YEAR LIMITED WARRANTY.

OVERALL DIMENSIONS

32' wide x 8' tall x 8.0" depth

WEIGHT

Hanging weight: 1700 lbs

Shipping weight: 2300 lbs

CONSTRUCTION

22-gauge galvanized steel cabinet with powder coat finish for strength, durability, and lasting appearance

POWER REQUIREMENTS

Scoreboard:

(1) 20-amp, 120-volt, 60-hertz, grounded AC circuit connected to an ON/OFF switch and/or circuit breaker

Controller:

Standard LCD controller powered by 12V DC Adapter or an optional internal battery.

SCORING INFORMATION DISPLAYED

HOME and GUEST: 2 - digit displays, 0-99

TO GO: 2 - digit display, 0-99

BALL ON: 2 - digit display, 0-99

HOME & GUEST TIME OUTS: 1-digit display 0-9

DOWN and QUARTER: 1 - digit display, 0-9

CLOCK: 4 - digit displays, counts up or down, 99:59-00:00 or 00:00-99:59

POSSESSION INDICATORS: 2 - football displays

CAPTIONS

HOME and GUEST: 15.0" tall

TO GO: 12.0" tall

DOWN: 12.0" tall

BALL ON: 12.0" tall

QTR: 12.0" tall

CLOCK COLON: 3.5" tall

Polymeric Calendared Vinyl Lettering

CLOCK Display

30.0" tall, 160° visibility, red, 100,000 hour-rated, outdoor Super-Bright LED (light emitting diode) displays
Impact Resistant Acrylic Protective Digit Shields and Adjustable LED Intensity Included

HOME, GUEST, , DOWN, TO GO, BALL ON, and QTR Display

24.0" tall, 160° visibility, red, 100,000 hour-rated, outdoor Super-Bright LED (light emitting diode) displays
Impact Resistant Acrylic Protective Digit Shields and Adjustable LED Intensity Included

TIME OUTS Display

18.0" tall, 160° visibility, red, 100,000 hour-rated, outdoor Super-Bright LED (light emitting diode) displays
Impact Resistant Acrylic Protective Digit Shields and Adjustable LED Intensity Included

POSSESSION Displays

6.5" tall football indicators, 160° visibility, red, 100,000 hour-rated, outdoor Super-Bright LED (light emitting diode) displays

Impact Resistant Acrylic Protective Digit Shields and Adjustable LED Intensity Included

APPROVALS

ETL/CSA listed

Scoreboard: Meets all FCC Class A requirements

2.4GHz wireless transmitter: FCC Part 15 certified

2.4GHz wireless receiver: Meets all FCC Part 15 requirements

WARRANTY

This product is warranted against defects in materials and workmanship for a period of five (5) years from the date of invoice. This includes factory repair service for parts covered under warranty. Complete warranty details are included on the CD shipped with each unit.

SERVICE

Technical Support is available 24 hours a day, 7 days a week

An access panel on the back of the scoreboard allows easy access to the electronic module, (the only working part of the scoreboard), for ease of replacement/servicing. These universal, plug-in electronic modules are used in all of the manufacturer's scoreboards using outdoor LED displays, and are 100% interchangeable between any of the manufacturer's outdoor, permanent LED scoreboards. If you have any question contact us at (888) 241-6603 x3 during business hours or 24/7 at service@optecsansi.com.

INSTALLATION

This model may be installed between (3) 8" OD steel, schedule 40 poles; or (3) 8" I-beams, minimum. Hole depth /diameter as well as pole/concrete specifications must be based on customer's local building codes, soil conditions, and wind loads. Mounting rails are supplied.

Support structure and mounting hardware supplied by installer/others

SCOREBOARD CONTROLLER

Dimensions: 2.5" height x 14.0" width x 7.0" depth.

Weight: 2.10 lbs.

The keyboard controller available with this scoreboard is microprocessor-controlled, molded of high-impact ABS plastic, has a tactile membrane keypad. Options include 2.4GHz wireless control and external battery pack with automatic battery charger.

Cable-Controlled System (standard) Includes:

- (1) Keyboard controller
- (3) FOOTBALL keypad inserts
- (1) Junction box cover with receptacle (to be installed at scorekeeper's location)
- (1) 20-ft. signal cable (used to connect the keyboard to the junction box receptacle)
- (1) Project-specific length of 4 wire twisted pair, shielded control cable

2.4GHz Wireless System (optional) Includes:

- (1) Universal LCD keyboard controller (internal battery pack with built-in charger)
- (3) FOOTBALL keypad inserts
- (1) 12-volt DC wall transformer
- (1) 2.4GHz transmitter (connects to keyboard controller via supplied interface cable)
- (1) 2.4GHz receiver (connects to the scoreboard, eliminating control cable and junction box installation)

OPTIONS

- Wireless remote control system
- Wireless remote control battery option
- Solar- charged battery power
- Electronic team names
- Horn
- Message center
- Controller carry case
- Conversion kit for baseball
- Conversion kit for Soccer
- Conversion kit for track
- Sponsor panel(s)

SCOREBOARD DIMENSIONS:
32' wide X 8'tall X 8" depth

